

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) An image sensing apparatus comprising:

an image sensing unit, which includes a honeycomb-type solid-state electronic image sensor, for sensing ~~the~~ an image of a subject to thereby output image data representing the image of the subject, said honeycomb-type solid-state electronic image sensor having a number of photoelectric transducers disposed in column and row directions, wherein the photoelectric transducers for odd-numbered columns are placed in odd- or even-numbered rows and the photoelectric transducers for even-numbered columns are placed in even- or odd-numbered rows;

a first recording controller for recording image data, which is output from said image sensing unit, on a recording medium; and

a second recording controller for recording data, which represents characteristics based on ~~the~~ a structure of lenses of the honeycomb-type solid-state electronic image sensor, on the recording medium in association with the image data.

2. (Currently Amended) The apparatus according to claim 1, further comprising a storage device for storing the data representing the characteristics;

wherein said second recording controller records the data representing the characteristics on ~~the~~ a storage medium, said data being read out of said storage device.

3. (Currently Amended) A method of controlling operation of an image sensing apparatus, comprising the steps of:

sensing the an image of a subject and obtaining image data representing the image of the subject using a honeycomb-type solid-state electronic image sensor having a number of photoelectric transducers disposed in column and row directions, wherein the photoelectric transducers for odd-numbered columns are placed in odd- and even-numbered rows and the photoelectric transducers for even-numbered columns are placed in even- or odd-numbered rows;

recording the obtained image data on a recording medium; and

recording data, which represents characteristics based on the a structure of lenses of the honeycomb-type solid-state electronic image sensor, on the recording medium in association with the image data.

4. (Cancelled)

5. (Previously Presented) The image sensing apparatus according to claim 1, wherein said second recording controller further records data representing circuit characteristics based on the use of the honeycomb-type solid-state electronic image sensor on the recording medium.

6-7. (Cancelled)

8. (Previously Presented) The method according to claim 3, wherein said step of recording data further records data representing circuit characteristics based on the use of the honeycomb-type solid-state electronic image sensor on the recording medium.

9. (Cancelled)

10. (New) The apparatus according to claim 1, wherein the structure of the lenses is on-chip-lens curvature.

11. (New) The apparatus according to claim 1, wherein the structure of the lenses is index of refraction and position.

12. (New) The apparatus according to claim 1, wherein the structure of the lenses is inner-lens curvature.

13. (New) The apparatus according to claim 1, wherein the structure of the lenses is aberration.

14. (New) The apparatus according to claim 13, wherein the aberration is distortion.

15. (New) The apparatus according to claim 13, wherein the aberration is chromatic magnification.